



THUNDER

Industrial T9[®] Keypad Handheld

Thunder

Industrial T9[®] Keypad Handheld

The Thunder industrial handheld features a combination of connectivity options and standard features such as a dedicated GNSS receiving board, DB9 Series COM Port, Long Range Bluetooth, NFC, Wi-Fi and 3G. This provides a complete solution for high-accuracy GIS applications in any environment. The IP rating of this receiver makes it suitable for field use. The Thunder Industrial Handheld comes ready for work with application possibilities ranging from power, agriculture and geological industries to forestry, field service and GIS/Surveying.

Specification

		T17N	T17	T17M	T17T
Overview	Processor	806MHz			
	ROM	4GB			
	RAM	512MB			
	Operation System	Windows Mobile 6.X			
	Multi-Language	√			
	Keypad	27 numeric + programmable keys			
	Mic	√			
	Speaker	$\sqrt{}$			
	Display	3.7" sunlight readable with integrated touch screen			
	Display resolution	480 x 640			
	Camera	5 megapixel			
	Dimension	200mm x 96mm x 32mm			
	Weight	515g with battery			
GNSS Performance	GPS L1	orog mar battery	√	V	V
	BDS B1		, , , , , , , , , , , , , , , , , , ,		· ·
	GLONASS L1		ì	GPS+BD/GPS+GLONASS	GPS+BD/GPS+GLONASS
	Channels	_	167	72	72
	Raw Data		- 107	-	√ √
	NMEA-0183			- V	√
	External antenna		√ √	√	√
Acquirect	Autonomous		3m	2.5m	2.5m
Accuracy (Internal Accord accuracy)	SBAS	-	2.5m	2.5III	2.5III 2m
	DGPS		2.5111	1.5m	1.5m
,,	Hot start		- 1s	1.5III	1.5iii
Time to First Fix	Warm start	-	29s	27s	27s
	Cold start		29s 29s	27s	27s
	Re-acquisition		295 1s	1s	1s
	Bluetooth 2.1 class II	V	15	15	15
Communications and Data Storage	Long range Bluetooth	Optional (along with standard bluetooth)			
	NFC	Optional (along with standard bluetooth)			
	GSM/3G (WCDMA)	3G (WCDMA)			
	WIFI	JG (WCDMA)			
	USB port	Type B USB			
	Serial port	DB9			
	Voice	-			
		TF card, up to 32GB			
Power	Storage extension				
	DC input	DC 5V, 1A 6 500mAh 3 7V			
	Detachable Li-ion battery				
Environment Specification	Operating temperature	- 20°C ~ +60°C			
	Storage temperature	- 30°C ~ +70°C			
	Sand, dust&water	IP54			
	Drop	1.2m protection			
Accessory	Standard accessory	DC adapter, USB cable, Serial cable, Battery, Strap with Stylus, Screen protection film and User guid(Electronic Edition			
	Optional accessory	Mounting bracket and Pole (Claw) Clamp, External GNSS antenna, External antenna cable			



